




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>B60R 21/16</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/50271</b> (43) International Publication Date: <b>31 August 2000 (31.08.00)</b>
<p>(21) International Application Number: <b>PCT/US00/04678</b></p> <p>(22) International Filing Date: <b>24 February 2000 (24.02.00)</b></p> <p>(30) Priority Data: <b>09/258,425</b>      <b>26 February 1999 (26.02.99)</b>      <b>US</b></p> <p>(71) Applicant: <b>LEAR CORPORATION [US/US]; 21557 Telegraph Road, Southfield, MI 48034 (US).</b></p> <p>(72) Inventor: <b>KOJWALSKI, Edward, L.; 709 Snowmass Drive, Rochester Hills, MI 48309 (US).</b></p> <p>(74) Agents: <b>QUINN, Christopher, W. et al.; Brooks &amp; Kushman, 1000 Town Center, 22nd floor, Southfield, MI 48075 (US).</b></p>		<p>(81) Designated States: <b>European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b></p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: <b>VEHICLE FLOOR SYSTEM INCORPORATING AIRBAG</b></p>		
<p>(57) Abstract</p> <p>A vehicle safety system includes a floor pan (16), an inflatable airbag (24) and inflator (30) integrated into the carpet (18) and positioned on the floor pan (16). The airbag (24) is positioned on the floor pan (16) in a footwell (20) area to selectively raise the foot of a vehicle occupant when the airbag (24) is deployed.</p> 		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## VEHICLE FLOOR SYSTEM INCORPORATING AIRBAG

### TECHNICAL FIELD

The present invention relates to a vehicle flooring system incorporating an airbag for raising the feet of a vehicle occupant upon impact to prevent engagement of the feet with the vehicle toe pan.

### BACKGROUND ART

Offset frontal crash testing results published by NHTSA suggests that the lower extremities of the test dummies may be exposed to significant forces upon impact. This test dummy injury data is a result of encroachment of the toe pan into the footrest area of the vehicle front seats.

Accordingly, it is desirable to minimize the affects of toe pan encroachment into the front seat footrest areas of a vehicle.

### DISCLOSURE OF INVENTION

The present invention relates to a vehicle safety system in which an airbag and inflator assembly are integrated into the carpet of a vehicle in a footrest area in order to raise the foot or feet of a vehicle occupant on impact to prevent engagement of the lower extremities of the occupant with the toe pan of the vehicle in a frontal impact. The airbag is covered by a flat protective plate to prevent puncture.

More specifically, the present invention provides a vehicle safety system, including a floor pan, and an inflatable airbag and inflator assembly integrated into the carpet on the floor pan. The integrated carpet/airbag system is positioned on the floor pan in a footwell area to selectively raise the foot of a vehicle occupant when the airbag is deployed. The airbag and inflator assembly is secured to the carpet by a foam-in-place operation.

Preferably, a protector plate is positioned between the airbag and the carpet in order to protect the airbag from puncture, such as by the heel of a shoe. Also, the airbag assembly is preferably sealed to prevent moisture entry.

5 Accordingly, an object of the invention is to provide a vehicle safety system in which an airbag is deployable from underneath the carpet to raise the feet of a vehicle occupant upon impact.

The above object and other objects, features and advantages of the present invention are readily apparent from the following detailed description of the best mode for carrying out the invention when taken in connection with the  
10 accompanying drawings.

### BRIEF DESCRIPTION OF DRAWINGS

FIGURE 1 shows a schematically arranged perspective view of a vehicle incorporating an integrated carpet/airbag system in accordance with the present invention;

15 FIGURE 2 shows a longitudinal cross-sectional view of the integrated carpet/airbag system shown in Figure 1;

FIGURE 3 shows a longitudinal cross-sectional view of the integrated carpet/airbag system of Figure 2 with the airbag deployed;

20 FIGURE 4 shows a plan view of the airbag and inflator assembly shown in Figure 1; and

FIGURE 5 shows a perspective view of the airbag and inflator assembly of Figure 4 with the airbag inflated.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Figures 1 and 2 show a vehicle 10 incorporating an integrated carpet/airbag safety system 12 in accordance with the present invention. As shown, an integrated carpet/airbag safety system 12 comprises an inflatable airbag assembly 14 integrated into the carpet 18 on the floor pan 16 in a footwell area 20 of the vehicle floor.

As illustrated in Figure 2, foam padding 22 is provided between the airbag assembly 14 and the carpet 18. The foam is used to retain the airbag assembly 14 and inflator 30 onto the carpet, thereby integrating these components into the carpet. This is performed by a foam-in-place operation in which the airbag assembly 14 and inflator 30 are laid in a mold with the carpet, and foam 22 is sprayed therearound. The mold is closed and the foam expands to fill all areas. The foam 22 adheres to the carpet 18 and the airbag assembly 14 and inflator 30, thereby forming the integrated carpet/airbag safety system 12.

The airbag assembly 14 comprises an airbag 24 positioned between a protective upper plate 26 and a bottom plate 28. The protective upper plate 26 is preferably a hard plastic material, such as ABS, in order to protect the airbag 24 from puncture, such as from a heel of a shoe. The protective upper plate 26 and bottom plate 28 are preferably sealed, such as by shrinkwrapping or any other known seal, in order to protect the airbag 24 from moisture.

As shown in Figures 4 and 5, the inflator 30 is connected to the airbag 24 by an elbow 32 for inflating the airbag 24 to the position shown in Figures 3 and 5, wherein the carpet 18 is raised. In the collapsed position shown in Figure 2, the airbag assembly 14 has an overall thickness of approximately 10mm, and in the deployed position of Figure 3 the airbag assembly 14 has an overall thickness of approximately 60mm. In this configuration, the foot of a vehicle occupant is raised in order to prevent engagement of the lower extremities of the vehicle occupant with the toe pan of the vehicle in the event of a frontal impact.






While the best mode for carrying out the invention has been described in detail, those familiar with the art to which this invention relates will recognize various alternative designs and embodiments for practicing the invention within the scope of the appended claims.

**WHAT IS CLAIMED IS:**

1. A vehicle safety system comprising:  
a floor pan;  
an inflatable airbag and inflator integrated into a carpet and positioned  
5 on the floor pan;  
wherein said airbag is positioned on the floor pan in a footwell area  
to selectively raise the foot of a vehicle occupant when the airbag is deployed.
2. The vehicle safety system of claim 1, wherein the airbag and  
inflator are secured to the carpet by foam.
- 10 3. The vehicle safety system of claim 1, further comprising a  
protector plate positioned between the airbag and the carpet to protect the airbag.-
4. The vehicle safety system of claim 3, further comprising a  
bottom plate cooperating with the protector plate to enclose the airbag.
- 15 5. The vehicle safety system of claim 4, wherein said bottom plate  
and protector plate are sealed to protect the airbag from moisture.
6. The vehicle safety system of claim 1, wherein the airbag  
comprises a thickness of approximately 10mm before deployment and approximately  
60mm after deployment.
- 20 7. A vehicle flooring system comprising:  
a carpet positioned in a footwell area of the vehicle; and  
an inflatable airbag and inflator integrated into the carpet in the  
footwell area to selectively raise the foot of a vehicle occupant when the airbag is  
deployed.

8. The flooring system of claim 7, further comprising a protector plate positioned between the airbag and the carpet to protect the airbag from puncture.
9. The flooring system of claim 7, wherein said inflatable airbag and inflator are secured to the carpet by foam.
- 5



*Fig. 1**Fig. 2**Fig. 3**Fig. 4**Fig. 5*

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 00/04678

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60R21/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B60R B60N B62D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 04, 30 April 1999 (1999-04-30) & JP 11-011242 A (HONDA MOTOR CO LTD), 19 January 1999 (1999-01-19) abstract	1,3-8
X	DE 197 27 598 A (VOLKSWAGENWERK AG) 7 January 1999 (1999-01-07) column 3, line 40 -column 4, line 34; figures 1,3,5	1,3,4,7, 8
X	GB 2 315 713 A (AUTOLIV DEV) 11 February 1998 (1998-02-11) page 4, line 24 -page 5, line 25; figures 1,2	1,3,7,8
	---	
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

3 July 2000

Date of mailing of the international search report

11/07/2000

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentean 2  
NL - 2280 HV Rijswijk  
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Eklom, H

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 00/04678

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 196 39 467 C (PARS PASSIVE RUECKHALTESYSTEME) 8 January 1998 (1998-01-08) column 4, line 29 - line 41; figure 1	1,7
P,X	DE 298 23 235 U (TRW REPA GMBH) 29 April 1999 (1999-04-29) page 10, line 13 - line 25; figure 8	1,3-8

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/04678

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 11011242 A	19-01-1999	NONE	
DE 19727598 A	07-01-1999	NONE	
GB 2315713 A	11-02-1998	EP 0915782 A WO 9805534 A	19-05-1999 12-02-1998
DE 19639467 C	08-01-1998	AU 4301297 A DE 19756430 A WO 9813226 A	17-04-1998 01-07-1999 02-04-1998
DE 29823235 U	29-04-1999	NONE	